

Segmentation

Leonid I. Dimitrov and Miloš Šrámek
Commission for Scientific Visualization
Austrian Academy of Sciences

Viscom/OAW

4/10/00
1

What Is Segmentation?

- The process of isolating objects of interest from the rest of the scene (Castleman, 1979)
- The process of partitioning an image into non-intersecting regions such that each region is homogeneous and the union of no two adjacent region is homogeneous (Pal, 1993).

Viscom/OAW

4/10/00
2

Why Is It Useful?

- Extracts information
- Enhances contents
- Enables measurements
- Provides guidance
- Allows comparisons

Viscom/OAW

4/10/00
3

Why Is It Difficult?

- Non-uniform mapping
- Inhomogeneities
- Inadequate object model
- Spurious artefacts
- Noise

Viscom/OAW

4/10/00
4

Tomographic Data and Segmentation

- Many anatomically distinct objects
- High variability of object shapes
- High variability of scanner parameters
- 3D objects' nature
- High demands on the segmentation precision
- No control over the environment

Viscom/OAW

4/10/00
5

Segmentation Methods

- Automatic
 - Many approaches
 - Still a problem
- Semiautomatic
 - Most popular
 - Usually hierarchical
- Manual
 - Totally subjective
 - Only for simple tasks

Viscom/OAW

4/10/00
6

Segmentation Methods

- Automatic
 - Processing of numerous data sets
 - Tuning to specific tasks (brain from MRI data)
 - Special parameter settings
 - Necessity of visual verification
- Semiautomatic
 - Based on user's knowledge & experience
 - Highly precise
 - Labor-intensive
 - 2D (slice) and 3D (volume) approaches

4/10/00
7

Viscom/OAW

Segmentation Methods

- 2D-techniques
 - Manual editing by paintbrush tools
 - Thresholding
 - Active contours (snakes)
 - Problems with 3D anatomy
- 3D-techniques
 - Histogram-based
 - Connected-components labeling
 - Active surfaces (balloons)
 - Problems with anatomically distinct objects

4/10/00
8

Viscom/OAW

Segmentation Methods

- Image-based
 - Rely only on image properties
 - Usually multistage approach
- Knowledge-based
 - Use explicit information
 - No distinction to registration

4/10/00
9

Viscom/OAW

Image-based Segmentation Methods

- Discontinuity-oriented
 - Geometric features
 - Boundary detection
 - Edge linking
- Similarity-oriented
 - Thresholding
 - Region-growing
 - Motion use

4/10/00
10

Viscom/OAW

Geometric Features

- Use discontinuities in the image to isolate distinct elements:
 - Points
 - Lines
 - Edges

4/10/00
11

Viscom/OAW

Point Detection

-1	-1	-1
-1	8	-1
-1	-1	-1

$$R = w_1 z_1 + w_2 z_2 + \dots + w_9 z_9 = \sum_{i=1}^9 w_i z_i$$

A point is detected if $|R| > T$ where
 T is a nonnegative threshold

4/10/00
12

Viscom/OAW

Line Detection

-1	-1	-1	-1	-1	2	-1	2	-1	2	-1	-1
2	2	2	-1	2	-1	-1	2	-1	-1	2	-1
-1	-1	-1	2	-1	-1	-1	2	-1	-1	-1	2

The above masks can be used for detecting lines of a particular slope.

Viscom/OAW

4/10/00
13

Edge Detection

- An edge is the boundary between two regions with distinct gray level properties.
- Edge-detection techniques rely on derivative operators.
- This is the most common approach for detecting meaningful discontinuities.

Viscom/OAW

4/10/00
14

Gradient Vector and Magnitude

- Image: $f(x, y)$
- Gradient: $\nabla f(x, y) = \begin{bmatrix} G_x \\ G_y \end{bmatrix} = \begin{bmatrix} \frac{\partial}{\partial x} f \\ \frac{\partial}{\partial y} f \end{bmatrix}$
- Magnitude: $|\nabla f| = \sqrt{G_x^2 + G_y^2}$

Viscom/OAW

4/10/00
15

Gradient Direction and Approximation

- Direction: $\alpha(x, y) = \tan^{-1} \left(\frac{G_y}{G_x} \right)$
- Approximation: $\nabla f(x, y) = |G_x| + |G_y|$

Viscom/OAW

4/10/00
16

Gradient Operators



Sobel

Roberts

Viscom/OAW

4/10/00
17

Gradient Operators



Prewitt

Isotropic

Viscom/OAW

4/10/00
18

Sobel Operators

- Used to compute the derivatives:

-1	-2	-1
0	0	0
1	2	1

-1	0	1
-2	0	2
-1	0	1


- In formulas:

$$G_x = (z_7 + 2z_8 + z_9) - (z_1 + 2z_2 + z_3)$$

$$G_y = (z_3 + 2z_6 + z_9) - (z_1 + 2z_4 + z_7)$$

4/10/00
19


Sobel Operators



original gradient

4/10/00
20

Sobel Operators



x-gradient y-gradient

4/10/00
21

Edge Linking – Local Processing

- Analyze and link pixels with similar characteristics in a small neighborhood about every detected point:
 - 4-connected
 - 8-connected
 - m-connected

4/10/00
22

4-Connectivity

- Pixels p and q are 4-connected if $q \in N_4(p)$

0	1	1
0	1	0
1	0	1

4/10/00
23

8-Connectivity

- Pixels p and q are 8-connected if $q \in N_8(p)$

0	1	1	1
1	0	1	1
1	0	0	0
1	0	0	1

4/10/00
24

m-Connectivity

- Pixels p and q are m -connected if
 - 1) $q \in N_4(p)$ or 2) $q \in N_8(p) \wedge N_4(q) \cap N_4(p) = \{\}$

0	1	1	1
1	0	1	1
1	0	0	0
1	0	0	0

Viscom/OAW

4/10/00
25

Edge Linking – Gradient-based

- Compare gradient strength:

$$f(x, y) \approx f(x', y') \Leftrightarrow |\nabla f(x, y) - \nabla f(x', y')| \leq T$$
- Compare gradient angle:


$$f(x, y) \approx f(x', y') \Leftrightarrow |\alpha(x, y) - \alpha(x', y')| \leq A$$

Viscom/OAW

4/10/00
26

Edge Linking – Global Processing

- Hough transform: finds pixels lying on a parameterized curve of a predefined shape



Viscom/OAW

10/00
27

Region-oriented Segmentation

- Partition the entire image R in n subregions R_i such that:
 - 1) $R = \bigcup_{i=1}^n R_i$
 - 2) R_i is connected
 - 3) $R_i \cap R_j = \{\}$ for $i \neq j$
 - 4) $P(R_i) = \text{TRUE}$ for $i = 1, 2, \dots, n$
 - 5) $P(R_i \cup R_j) = \text{FALSE}$ for $i \neq j$

$P(R_i)$ is a logical predicate

Viscom/OAW

4/10/00
28


Thresholding

- Labeling operation on a gray scale image that distinguishes pixels of a higher intensity from pixels with a lower intensity value
- The output is usually a binary image.
- Works well when the image histogram is bi-modal.

Viscom/OAW

4/10/00
29



Thresholding



Viscom/OAW

4/10/00
30

Thresholding

CT data
MRI data

Viscom/OAW 4/10/00
31

Thresholding

- Global thresholding
- Local thresholding
- Multiple thresholding
- Dynamic thresholding
- Optimal thresholding

Viscom/OAW 4/10/00
32

Region Growing

- Group pixels or subregions into larger regions
 - Pixel aggregation
- Two problems:
 - Selection of initial seeds
 - Selection of suitable properties

Viscom/OAW 4/10/00
33

Region Splitting and Merging

- Split into four disjointed quadrants any region R_i where $P(R_i) = \text{FALSE}$
- Merge any adjacent regions R_i and R_j for which $P(R_i, R_j) = \text{TRUE}$
- Stop when no further merging or splitting is possible

Viscom/OAW 4/10/00
34

Mathematical Morphology

- Describes objects as subsets of Euclidean space, emphasising their shapes, volumes, textures, i.e. reduces them to their essentials. It classifies the objects into groups by putting them through a sequence of set transformations (J. Serra, 1982).
- It is a hybrid mixture of abstract mathematics (set theory) and reliable recipes.

Viscom/OAW 4/10/00
35

Mathematical Morphology

- Describes images as sets of ordered pairs (coordinates): $A, B \subset Z^2$
- Transformations are set operations:
 - Dilation: $A \oplus B = \{x | B_x \cap A \neq \emptyset\}$
 - Erosion: $A \otimes B = \{x | B_x \subseteq A\}$
 - Opening: $A \circ B = (A \otimes B) \oplus B$
 - Closing: $A \bullet B = (A \oplus B) \otimes B$

Viscom/OAW 4/10/00
36

